



DRIVE-OVER CURB DETAIL

NOTES

1. FINE HAIR BRUSH FINISH ON CURB, GUTTER, AND SIDEWALK.
2. CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE APPLICABLE SECTIONS OF THE CURRENT CITY OF RIPON SPECIFICATIONS.
3. CONSTRUCT EXPANSION JOINTS 200' C.C. MAXIMUM, AT CURB RETURNS, AT CATCH BASINS, AND AT BOTH SIDES OF DRIVEWAYS.
4. MATERIAL UNDER SIDEWALK AND GUTTER SHALL BE COMPACTED TO 95% RELATIVE COMPACTION FOR A DEPTH OF 8".
5. IN THE SIDEWALK AREA, TRANSVERSE SCORE MARKS SHALL BE SPACED AT 6' ON CENTER.
6. CONCRETE PAVER STREETS WILL HAVE A VERTICAL GUTTER REVEAL.

NO.	REVISED	BY	4-1/2" Drive-Over Curb, Gutter, and Sidewalk	APPROVED
				 CITY ENGINEER RCE-28191
				DATE: 2-2-99
DRAWN BY: MCP			CITY OF RIPON	STANDARD NO. ST-21a
CHECKED BY: DJR				
<small>V:\125 City of Ripon Standards\Standard Specifications\Drawings\Streets\st-21a.dwg</small>				