



NOTES:

1. SET MONUMENT, FRAME AND COVER AFTER PAVEMENT IS IN PLACE.
2. MONUMENT FRAMES AND COVERS SHALL BE TOUGH GREY IRON CASTING CONFORMING TO THE LATEST A.S.T.M. REQUIREMENTS. EACH COVER SHALL BE GROUND OR OTHERWISE FINISHED SO THAT IT WILL FIT IT'S FRAME WITHOUT ROCKING.
3. FRAME AND COVER TO BE PINKERTON FOUNDRY NO. A-581M, AMERICAN BRASS AND IRON FOUNDRY, OR EQUAL. CAST IRON COVER TO BE MARKED MONUMENT.
4. MONUMENTS TO BE SET AT ALL INTERSECTIONS, ENDS OF CUL-DE-SACS, AT B.C. & E.C. OF CURVES AND AT ENDS OF SUBDIVISION. ON LONG TANGENTS, THE MAXIMUM DISTANCE BETWEEN MONUMENTS SHALL NOT EXCEED 800'. MONUMENTS SHALL BE EQUALLY SPACED.

NO.	REVISED	BY	Survey Monument	APPROVED	
				<i>Dee L. Brown</i>	CITY ENGINEER RCE-28191
DRAWN BY: TP				DATE: 2-2-99	
CHECKED BY: DJR				STANDARD NO. M-3	
SCALE: NONE			CITY OF RIPON		