



NOTES

1. FINE HAIR BROOM FINISH ON CURB, GUTTER, AND SIDEWALK.
2. CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE APPLICABLE SECTIONS OF THE CURRENT CITY OF RIPON SPECIFICATIONS.
3. CONSTRUCT EXPANSION JOINTS 200' C.C. MAXIMUM, AT CURB RETURNS, AT CATCH BASINS, AND AT BOTH SIDES OF DRIVEWAYS.
4. MATERIAL UNDER SIDEWALK AND GUTTER SHALL BE COMPACTED TO 95 % RELATIVE COMPACTION FOR A DEPTH OF 8".
5. IN THE SIDEWALK AREA, TRANSVERSE SCORE MARKS SHALL BE SPACED AT 6' ON CENTER.
6. 5 (FIVE) 5/8" x 24" LONG STEEL DOWELS GREASED AND WRAPPED, ONE SIDE, THRU EVERY EXPANSION JOINT.

NO.	REVISED	BY	Class II Bicycle Path and Gutter Pan	APPROVED
				 CITY ENGINEER RCE-58093
				DATE: 12-4-2001
DRAWN BY: MCP			CITY OF RIPON	STANDARD NO. ST-21c
CHECKED BY: MJM				
<small>V:\25_City of Ripon Standards\Standard Specifications\Drawings\Streets\st-21c.dwg</small>				